



Chemlube Premium Gold 10W-40 API SN

Chemlube Premium Gold passenger car engine oils are formulated for Turbo-charged and naturally aspirated gasoline, propane, natural gas engines in passenger car and light duty truck service. They exceed API SN and previous service categories. They are designed for use in U.S., European, and Japanese passenger cars, vans, sport utility vehicles and light duty trucks containing gasoline or turbo charged engines.

Features

- Exceeds API Service SN.
- Meets passenger car and light truck manufacturers warranty requirements.
- Lubricates, cools, and protects turbo-charged high-revving engines that operate at high temperatures.
- Protects the engine in controlling varnish, deposits, rust, corrosion, wear, and cleanliness.
- Reduces high temperature oxidation.
- Energy-Conserving for improved fuel economy.

Applications

- Passenger car and truck gasoline, propane, and natural gas engines specifying API service SN engine oils.
- Maintains the warranty requirements for today's passenger car and light duty trucks.

SAE 10W-40 TYPICAL PROPERTIES

Kinematic Viscosity	
cSt @ 40° C (D445)	106.90
cSt @ 100° C (D445)	15.68
Viscosity Index (D2270)	155
Flash Point (D92), ° C	202
Pour Point, (D97), ° C	-30
Color (ASTM)	3.5

NOTE: Values are typical only. Due to ongoing research, development and product improvement, product formulas are subject to change without notice. Chemlube International can not know all the uses this product may be subject to so it is the user's responsibility to ascertain that it is suitable for an intended use or application.

Contact: Chemlube International
 500 Mamaroneck Avenue
 Harrison, NY 10528 USA
 Tel: +1-914-381-5800; fax: +1-914-381-8988
 E-mail: info@chemlube.com
www.chemlube.com

