

PRODUCT DATA SHEET

A PRODUCT OF CHEMLUBE INTERNATIONAL, INC.



chemlube
INTERNATIONAL LLC

Chemlube Synthetic Multi-Vehicle Automatic Transmission Fluid

Application

- Chemlube Multi-Vehicle Transmission Fluid is a full *synthetic* automatic transmission fluid formulated to be suitable for use as a Service-Fill ATF for Asian step-automatic transmissions calling for Toyota T-III and Toyota T-IV, Honda Z-1, Nissan Matic D and Matic J and Mitsubishi SP-II and SP-III performance. Chemlube MVATF also meets the requirements of JASO 1A and other Asian OEM's like Hyundai, Subaru and Mazda. Suitable for use in automatic transmissions calling for GM DEXRON® IIIIG/H, DEXRON VI, Ford MERCON V® and Allison C-4. In addition, Chemlube MVATF meets the requirements of European OEM's such as ZF-TE-ML-14A, Voith 55.6335, MAN 339 Type Z-1 and MB, VW and BMW 4-and 5- speed automatic transmission specifications.

Features

- Performance demonstrated in standard industry and OEM tests
- Superior anti-shudder performance and durability
- Superior anti-wear protection.
- Superior clutch-shifting characteristics
- Superior oxidation control
- Superior friction performance

TYPICAL PROPERTIES

API Gravity	ASTM D4052	35.1
Viscosity		
@ 40°C, cSt	ASTM D445	37.0
@ 100°C, cSt	ASTM D445	7.2
Viscosity Index	ASTM D2270	162
Brookfield Viscosity	ASTM D2983	
cP @ -40°C		14,200
Flash Point, °C		180
Pour Point, °C	ASTM D97	-42
Color	ASTM D1500	Red

NOTE: Values are typical only. Due to ongoing research, development and product improvement, product formulas are subject to change without notice. Chemlube International can not know all the uses this product may be subject to so it is the user's responsibility to ascertain that it is suitable for an intended use or application.

Contact: **Chemlube International**
500 Mamaroneck Avenue
Harrison, NY 10528 USA
Tel: +1-914-381-5800; fax: +1-914-381-8988
E-mail: info@chemlube.com
www.chemlube.com

May-11 MVATF